

UNC-310L-B



Details of the UNC-310L-B 19" Rackmount chassis of the UNC-series	
Form-Factor:	mATX, ATX, EATX (suitable for SSI CEB 1.01 Dual Xeon)
Dimension (DxWxH):	690mm x 482,6mm x 132mm
Weight:	15 kg incl. Power Supply
External Drive Bays:	4x 5 1/4" 1x 3,5"
Internal Drive Bays:	2x 3,5"
Power Supply:	CHIEFTEC HPC-360-202-DF - 360 Watt
Fan(s) included :	3 x 80mm
Special Features:	Room, room, room in our lockable UNC-310L-B chassis, a Must-Have for the Entry-Level-Server business. Robust and secure for you and your hardware through deburred and twice chamfered edges as well as the usage of 1mm SECC steel and the provided dust cover. Perfect for small Web-, RAS- or Dev.-server. And that for a more favorable price, you can't avoid.
Included in delivery:	Power Cord, screwbag, Xeon cooler mounting plates, set of keys, dust filter, foam rubbers, ATX-I/O shield, binder, adhesive binder fastener, Power LED adaptor cable
Units per palette:	9 pieces

More UNC-310L-B models

UNC-310L-B-500	incl. 500W ATX12V, EPS12V, 120mm fan, active PFC
UNC-310L-B-550	incl. 550W ATX12V, EPS12V, 120mm fan, active PFC

Why should you choose this series:



Frontview closed:
dust filter behind booth grids, lock placed on the right door, Power- & HDD LED's



Fullview opened



Fullview closed
(blue foil, cover is metallic bright)



Frontview opened



Dustfilter left



USB connectors,
Power / HDD LED's,
On -/Off switch, Resetbutton.



Dustfilter right



80mm fanpreparation on top
of the protected cable hole,
80mm fan.



Fullview interior



80mm fanpreparation on top
of the protected cable hole



Dual Xeon fan mounting
plates



USB connector inside view



Scope of delivery



PCI-extensions



Mainboard area



On top of the ATX-I/O shield;
2 x 60mm fan preparation,
HDD Rahmen



Backside: 1x 80mm Fan, Power connector, I/O shield area, on top 2x 60mm fan preparation, PCI-slots

Accessories for our UNC-310L-B 19" Rackmount chassis:

Article	Description
SAA-122	SATA removable frame, fully made of aluminium, two fans
KF-21-IPF	U-DMA removable frame, frame made of aluminium, one fan
KF-22-IPF	U-DMA removable frame, frame made of aluminium, two fans
KF-23-IPF	U-DMA removable frame, frame made of aluminium, three fans
RSR-190	Mounting rails for 60cm deep 19" chassis
RSR-260	Mounting rails for 19" chassis
S-ATA-Cable	90° degree S-ATA cable, 50cm
ENH-0746GB	EPS12V ATX 2.0 460W Power Supply, suitable for Dual Xeon
SNT-2131SATA	SATA Backplane, 2HE for max. 3 SATA HDD's, hot-swappable
SNT-3141SATA	SATA Backplane, 3HE for max. 4 SATA HDD's, hot-swappable